

No.: GZIN1803013462CM

Date: Apr 10, 2018

Page: 1 of 8

CUSTOMER NAME:

S IGEPA group

Sample Name : Aluminum Composite Panel **B-bond**

Product Specification : 6mm

Above information and sample(s) was/were submitted and confirmed by the client. SGS, however, assumes no responsibility to verify the accuracy, adequacy and completeness of the sample information provided by client.

Date of Receipt

Mar 26, 2018

Testing Start Date

Mar 26, 2018

Testing End Date

Apr 10, 2018

Test result(s)

For further details, please refer to the following page(s)

(Unless otherwise stated the results shown in this test report refer only to

the sample(s) tested)

Signed for SGS-CSTC Standards Technical Services Co., Ltd. GZ Branch Testing

Center

Salon Liu

Authorized signatory





No.: GZIN1803013462CM

Date: Apr 10, 2018

Page: 2 of 8

Test Result Summary

Test(s) Requested	Result(s)	
EN 13501-1:2007+A1:2009 Fire classification of construction products and		
building elements-Part 1: Classification using data from reaction to fire tests	Classification: C-s1, d0	
Summary:	1	
1. For further details, please refer to the following page(s).		

×



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service prints overleaf, available on request or accessible at <a href="https://www.sps.com/en/Terms-and-Conditions.google.com/en/Terms-and-Condition

Attention/To check the authenticity of toaling / inspection report & certificate, please contact us at telephone: [86-755] 83
1443, or email: CN.Deccheck@sgs.com

198 Kaztu Raad, Scientach Park, Economic & Technical Development District, Guangshou, China. 510663 1 (86-20) 82155555 f (86-20) 82075080 www.sgs.group.com.cn 中国・广州・经济技术开发区科学城科珠路198号 邮編: 510663 t (88-20) 82155555 f (86-20) 82075080 e sgs.china@sgs.com



No.: GZIN1803013462CM

Date: Apr 10, 2018

Page: 3 of 8

TESTS AND RESULTS

Test Conducted:

This test is conducted as per EN 13501-1:2007+A1:2009 Fire classification of construction products and building elements- Part 1: Classification using data from reaction to fire tests. And the test methods as following:

- EN 13823:2010 Reaction to fire tests for building products Building products excluding floorings exposed to the thermal attack by a single burning item.
- 2. EN ISO 11925-2:2010+AC:2011 Reaction to fire tests-Ignitability of building products subjected to direct impingement of flame-Part 2: Single-flame source test.

Mounting and fixing (For EN 13823):

The specimen was tested free standing at a distance of at least 80 mm from the backing board. Both wings were clamped at the top and the bottom.

Test Results:

Test method	<u>Parameter</u>	Number of tests	<u>Results</u>
	FIGRA _{0.4MJ} (W/s)		249.4
	THR _{600s} (MJ)		4.8
	SMOGRA (m²/s²)		3.0
EN 13823:2010+A1:2014	TSP _{600s} (m ²)	3	14.5
	LFS < edge of specimen		Yes
	Flaming particles or droplets		No
EN ISO 11925-	<i>F</i> s ≤ 150 mm		Yes
2:2010+AC:2011 Exposure = 30 s	Ignition of the filter paper	6	No

Remark:

FIGRA-Fire growth rate index used for classification purposes [W/s]



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service prints overleaf, evaluable on request or accessible at http://www.ags.com/en/Tarms.and-Conditions.ago.and electronic format documents subject to Terms and Conditions for Electronic Documents at http://www.ags.com/en/Terms-en-Occument-ago-Attention is drawn to the limitation of itsiality, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of clients' instructions, if any. The Company's sole responsibility is to its Client and this document on ent exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approved of the Company, Any unauthorized alteration, forgery or faisification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this text report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

1443, or email: CN Ooccheck@sgs.com 198 Kazhu Road, Scientech Park, Economic & Technical Development District, Guergehou, China. 510663 1 (86-20) 82155555 「(86-20) 82075080 www.sgsgroup.com.cn 中国・广州・经济技术开发区科学域科森路198号 鄭纲: 510663 1 (86-20) 82155555 「(86-20) 82075080 e sgs.china@sgs.com



No.: GZIN1803013462CM

Date: Apr 10, 2018

Page: 4 of 8

For the classes A2 and B, FIGRA_{0.2}MJ
For the classes C and D, FIGRA_{0.4}MJ
LFS-Lateral flame spread m
THR_{600s}-Total heat release within 600 s MJ
SMOGRA-Smoke growth rate [m²/s²]
TSP_{600s}-Total smoke production within 600 s m²

Classification and direct field of application:

This classification has been carried out in accordance with EN 13501-1:2007+A1:2009.

Classification:

Fire behaviour		Smoke p	roduction		Flaming droplets	
С	-	s	1	7	d	0

Remark:

The classes with their corresponding fire performance are given in annex A.

Reaction to fire classification is based on the 7-step scale of A1 to F, where A1 is good and F is bad

Statement:

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire hazard of the product in use.

Warning:

This classification report does not represent type approval or certification of the product.

The test laboratory has, therefore, play no part in sampling the product for the test, although it holds appropriate references to the manufacturer's factory production control that is aimed to be relevant to the samples tested and that will provide for their traceability.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on requestor or accessible at http://www.ass.com/en/farms-and-Conditions.asp; and, for siectonic format documents subject to Terms and Conditions for Electronic Documents at http://www.ass.com/en/farms-and-Conditions/Terms-o-Document.asp. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information contained hereon reflects the Company's lindings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exponents parties to a frameaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced to the company of the company o



No. : GZIN1803013462CM

Date: Apr 10, 2018

Page: 5 of 8

Table 1 — Classes of reaction to fire performance for construction products excluding floorings and linear pipe thermal insulation products.

Class	Test method(s)		Classification criteria	Additional classification
	EN ISO 1182 ^a and		⊿ <i>T</i> ≤30°C, and	
A1			<i>∆m</i> ≤50%, and	-
			t _{f=} 0(i.e. no sustained flaming)	2
	EN ISO 1716		PCS≤2.0MJ/kg ^a and PCS≤2.0MJ/kg ^{bc} and PCS≤1.4MJ/m ^{2 d} and PCS≤2.0MJ/kg ^e	- "
A2	EN ISO 1182 ^a or		<i>∆T</i> ≤50°C, and	
		and	<i>∆m</i> ≤50%, and	1-
			t,≤20 s	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at https://www.sss.com/en/Terms-and-Conditions.sss.p...and, for electronic format documents applied to Terms and Conditions for Electronic Documents at <a href="https://www.sss.com/en/Terms-and-Conditions/Ter

1888 kah Red, Seriateh Zek, Economic Parkul Callengthou, China. 510663 1 (86-20) 82155555 1 (86-20) 82075080 www.sgsgroup.com.on 中国・广州・经济技术开发区科学域科珠路198号 節第: 510663 1 (86-20) 82155555 1 (86-20) 82075080 e sgs.china@sgs.com



No.: GZIN1803013462CM

Date: Apr 10, 2018

Page: 6 of 8

			DCCCO OMI/Icm 3		
	EN ISO 1716		PCS≤3.0MJ/kg ^a and PCS≤4.0MJ/m ² ^b and		
			PCS≤4.0MJ/m ^{2 d} and	-	
			PCS≤3.0MJ/kg ^e		
	EN 13823		FIGRA≤120W/s and LFS <edge and="" of="" specimen="" thr<sub="">600s≤7.5MJ</edge>	Smoke production ^f and Flaming droplets/particles ^g	
В	EN 13823 and		FIGRA≤120W/s and LFS <edge and<br="" of="" specimen="">THR600s≤7.5MJ</edge>	Smoke production f and Flaming droplets/particles g	
	EN ISO 11925-2 i Exposure =30s		Fs≤150mm within 60 s		
С	EN 13823 and	d	FIGRA≤250W/s and LFS <edge and<br="" of="" specimen="">THR600s≤15MJ</edge>	Smoke production f and Flaming droplets/particles g	
	EN ISO 11925-2 i Exposure=30s		Fs≤150mm within 60 s		
D	EN 13823 and	d	FIGRA≤750W/s	Smoke production f and Flaming droplets/particles g	
	EN ISO 11925-2 i Exposure=30s		Fs≤150mm within 60 s		
Е	EN ISO 11925-2 i Exposure =15s		Fs≤150mm within 20 s	flaming droplets/particles h	
F	No performance determined				

^a For homogeneous products and substantial components of non-homogeneous products.

^c Alternatively, any external non-substantial component having a PCS ≤ 2.0 MJ/m^2 , provided that the product satisfies the following criteria of EN 13823: FIGRA ≤ 20 W/s, and LFS < edge of specimen,



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed veryeries, available on request or accessible at the Newscale Section Farms and Conditions for Electronic Documents applications for Service printed subject to Terms and Conditions for Electronic Documents applications applications are supported to the Service Printed Service and Service Printed Service Service Printed Service Servi

^b For any external non-substantial component of non-homogeneous products.



No.: GZIN1803013462CM

Date: Apr 10, 2018

Page: 7 of 8

and THR_{600s} \leq 4,0 MJ, and s1, and d0.

^d For any internal non-substantial component of non-homogeneous products.

^e For the product as a whole.

fin the last phase of the development of the test procedure, modifications of the smoke measurement system have been introduced, the effect of which needs further investigation. This may result in a modification of the limit values and/or parameters for the evaluation of the smoke production.

s1 = SMOGRA \leq 30m²/s² and TSP_{600s} \leq 50m² ; s2 = SMOGRA \leq 180m²/s² and TSP_{600s} \leq 200m²; s3 = not s1 or s2

^g d0 = No flaming droplets/ particles in EN 13823 within 600 s;

d1 = no flaming droplets/ particles persisting longer than 10 s in EN 13823 within 600 s;

d2 = not d0 or d1.

Ignition of the paper in EN ISO 11925-2 results in a d2 classification.

^h Pass = no ignition of the paper (no classification);

Fail = ignition of the paper (d2 classification).

Under conditions of surface flame attack and, if appropriate to the end-use application of the product, edge flame attack.

SAMPLE INFORMATION AND PICTURES

Thickness: About 6mm

Mass per unit area: About 8.15kg/m²



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printer oversels, results on request or accessible at http://www.sps.com/en/Terms-and-Conditions.asps and, for inextonic format documents subject to Teste and on the company of the compa



No. : GZIN1803013462CM

Date: Apr 10, 2018

Page: 8 of 8





Before Test (EN 13823)

After Test (EN 13823)

Note: The above test was carried out by SGS-CSTC Standards Technical Services Co., Ltd. Shunde Branch. ******* End of report*******

