

Technical Datasheet

E334

TEXTILE WALL FABRIC / HIGHTACK ADHESIVE

GF 334 is a 210gsm premium white matte coated polyester fabric with a High-Tack Solvent adhesive, backed by a 120gsm DSPE Flat Liner. It is Suitable for indoor and outdoor advertising. The 120gsm release liner provides excellent stability for processing using standard solvent, eco-solvent, UV curable and latex digital inks common to wide format digital printing systems.

Applications: GF 334 is designed for temporary application of decals and graphics to most types of painted interior walls. This includes most flat, semi-gloss and gloss paint finishes. Decals may also be applied to sealed wall coverings. The surface must be smooth and clean prior to application. Not designed for coated/sealed/treated stainless steel, brass or bronze surfaces.

Weight: 210gsm (300Dx300D) $\pm$ 10%
Adhesive: 25mic High-Tack Solvent
Liner: 135 g/m² Liner

Application Temperature: Minimum application temperature $>+4,4^{\circ}\text{Celsius}$
Service temperature: -20°C to $+80^{\circ}\text{Celsius}$

Adhesion: 19N/25mm - FINAT TM 1, after 24 hours, adhered to stainless steel

Durability: Up to 3 years unprinted **

Recommendations: Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in vinyl degradation. * For UV Curable inks, please consult with the ink manufacturer for specifics on ink flexibility.

Fire rating: Self-extinguishing, adhered to stainless steel.
Shelf life: at 23°C / 50% moisture 2 years *

* Average Value

** Under vertical outdoor exposure, based on Central Europe Climate

Product Codes:	E334-54	137,2 cm X 30 m
	E334-60	152,4 cm X 30 m